

IN THE CLAIMS:

Please add new claim 13 as follows.

1. (Canceled).
2. (Previously Presented) A method according to claim 9, wherein
said reserving of transmission resources for handling non-real time traffic resides
in determining the difference between the overall available transmission resources of said
radio transceiver device of said radio access network and the transmission resources
required for handling real time traffic, wherein said difference is the reserved
transmission resources for the non-real time traffic.
3. (Previously Presented) A method according to claim 9, wherein
said step of obtaining and reserving is carried out repeatedly upon occurrence of
an update condition.
4. (Original) A method according to claim 3, wherein said update condition
resides in the lapse of an update period.
5. (Original) A method according to claim 3, wherein said update condition
resides in an entering of a RT bearer to the radio network or the leaving of an RT and/or
NRT bearer from the network.

6. (Original) A method according to claim 3, wherein said update condition resides in that a predetermined time of a day is reached.

7. (Previously Presented) A method according to claim 3, wherein
in a very first obtaining step, a predetermined value for the transmission resources required for handling real time traffic is used, and

in all subsequent obtaining steps, a detected value of the actually required transmission resources for handling real time traffic is used.

8. (Canceled).

9. (Previously Presented) A method for controlling transmission resources of a radio access network adapted to transmit data packets in real time traffic and in non-real time traffic, the method comprising the steps of:

obtaining information related to transmission resources required for handling real time traffic in a radio network controller; and

reserving transmission resources for handling non-real time traffic dynamically based on a knowledge of overall available transmission resources of a radio transceiver device of said radio access network and the information related to the transmission resources required for handling real time traffic by said radio transceiver,

wherein the respectively allocated reserved transmission resources are distinguished on the basis of ATM virtual path identifiers and virtual channel identifiers.

10. (Original) A method according to claim 9, wherein
said channel element identifiers are virtual path identifiers VPI and virtual
channel identifiers VCI.

11. (Previously Presented) A radio access network control device, configured to:
obtain information related to transmission resources required for handling real
time traffic in a radio network controller; and

reserve transmission resources for handling non-real time traffic dynamically
based on a knowledge of overall available transmission resources of a radio transceiver
device of said radio access network and the information related to the transmission
resources required for handling real time traffic by said radio transceiver,

wherein the respectively allocated reserve transmission resources are
distinguished on the basis of ATM virtual path identifiers and virtual channel identifiers.

12. (Previously Presented) A radio access network control device comprising:
obtaining means for obtaining information related to transmission resources
required for handling real time traffic in a radio network controller; and

reserving means for reserving transmission resources for handling non-real time
traffic dynamically based on a knowledge of overall available transmission resources of a
radio transceiver device of said radio access network and the information related to the
transmission resources required for handling real time traffic by the said radio

transceiver,

wherein the respectively allocated reserve transmission resources are distinguished on the basis of ATM virtual path identifiers and virtual channel identifiers.

13. (New) A radio transceiver device, configured to:

receive, from a radio access network control device, information relating to reserved transmission resources for handling non-real time traffic and for handling real time traffic, wherein the respectively reserved transmission resources are distinguished on the basis of ATM virtual path identifiers and virtual channel identifiers, and

use the reserved transmission resources for transmission, based on the ATM virtual path identifiers and virtual channel identifiers, by allocating respective traffic to corresponding channel elements distinguished on the basis of ATM virtual path identifiers and virtual channel identifiers.